

# Camlocks

## Easier and faster attaching and detaching!

Material Bronze Casting  
Stainless Steel (SCS14)  
Aluminium

Optional lever pins to prevent accidental detachment available.



Type D

Size	B	C	H	Rc
15A	44	25	48	1/2
20A	50	32	50	3/4
25A	60	37	58	1
32A	80	46	64	1-1/4
40A	89	54	68	1-1/2
50A	97	64	72	2
65A	110	76	77	2-1/2
80A	135	92	89	3
100A	165	120	94	4
125A	190	146	96	5
150A	254	176	108	6

Type A

Size	E	K	H	Rc
15A	13	27	38	1/2
20A	21	33	38	3/4
25A	24	39	46	1
32A	31	48	53	1-1/4
40A	39	56	53	1-1/2
50A	48	68	61	2
65A	60	83	72	2-1/2
80A	74	96	75	3
100A	102	124	77	4
125A	126	160	78	5
150A	152	185	84	6

Type B

Size	B	C	F	H	R
15A	44	25	14	47	1/2
20A	50	32	19	51	3/4
25A	60	37	26	60	1
32A	80	46	32	70	1-1/4
40A	89	54	38	72	1-1/2
50A	97	64	50	77	2
65A	110	76	65	85	2-1/2
80A	135	92	77	89	3
100A	165	120	101	93	4
125A	190	146	126	96	5
150A	254	176	146	110	6

Type F

Size	E	K	H	h	R
15A	13	27	53	25	1/2
20A	19	33	55	28	3/4
25A	25	41	66	34	1
32A	31	45	78	40	1-1/4
40A	38	53	78	41	1-1/2
50A	47	63	85	47	2
65A	58	83	100	49	2-1/2
80A	73	93	100	51	3
100A	102	121	108	51	4
125A	126	168	111	54	5
150A	152	185	126	56	6

Type E

Size	D	E	F	H
15A	24	13	8	??
20A	32	19	15	89
25A	37	24	20	106
32A	45	31	27	110
40A	53	38	33	112
50A	63	46	45	130
65A	76	60	51	141
80A	92	73	69	165
100A	120	102	92	178
125A	146	126	116	187
150A	176	155	144	210

Type C

Size	B	C	F	H
15A	44	25	8	67
20A	50	32	15	85
25A	60	37	20	97
32A	80	46	27	103
40A	89	54	33	108
50A	97	64	44	122
65A	110	76	56	138
80A	135	92	65	158
100A	165	120	90	165
125A	190	146	116	182
150A	254	176	144	204

Type DC

Size	B	C	H
15A	44	25	32
20A	50	32	35
25A	60	37	40
32A	80	46	46
40A	89	54	48
50A	97	64	50
65A	110	76	55
80A	135	92	57
100A	165	120	57
125A	190	146	59
150A	254	176	63

Type DP

Size	E	h	H
15A	13	26	38
20A	21	27	38
25A	25	31	44
32A	30	38	51
40A	38	38	51
50A	48	45	60
65A	60	46	63
80A	74	48	67
100A	102	48	68
125A	126	51	79
150A	155	56	85